

Performance of PEM Fuel Cell electrodes based on SWNT – Effect of Preparation Method

Federico A. Scodelaro¹, Leandro Balzano², Olga M. Matarredona² and Daniel E. Resasco^{1,2}

¹School of Chemical, Biological and Materials Engineering, University of Oklahoma, 100 E Boyd St, Norman, Oklahoma 73019

²Southwest Nanotechnologies Inc, 2360 Industrial Blvd, Norman, Oklahoma 73069

The objective of this work is to improve the performance of existing PEM fuel cells electrodes through the development and characterization of improved single-walled carbon nanotube-based electrocatalysts. Single-walled carbon nanotubes (SWNT) show great potential for improvement of fuel cell electrodes performances. In particular, they have a high surface area that can stabilize high Pt dispersions, they can increase the electronic conductivity of the electrodes, they can improve the gas transport rate through the electrodes reactive layers, and they can reduce peroxide attack of the ionomer.

SWNT-supported electrocatalysts were prepared by our proprietary method in which, by adjusting the pretreatment conditions and the pH of a SWNT dispersion, we can select the appropriate surface charge to favor anion or cation exchange with a Platinum precursor salt. In this way we have demonstrated that high loadings (20-30 wt%) of Pt with high dispersions (Pt nanoparticle sizes as low as 1-2 nm) could be achieved. These novel electrocatalysts have been physically characterized by EXAFS, XPS and TEM. The electrocatalytic activity was demonstrated by Cyclic Voltammetry.

Different methods have been used for the preparation of PEM Fuel Cell electrodes, mainly: 1) coating of catalyst ink on gas diffusion layer (GDL); 2) coating of catalyst ink directly over proton-exchange membrane and 3) using transfer decals (thin-film decal method) to apply catalyst ink over the membrane by hotpressing. A series of 5 cm² membrane-electrode assemblies have been prepared and their performance was tested at different temperatures, pressures and humidification levels by using a Fuel Cell Test Station.

Findings from this study indicate that the performance of the SWNT-based fuel cell electrodes is strongly related to the preparation method used, with the highest performance observed in the case of the Thin-Film decal method.